

A: Datasheet

Algorithm: vd_002

Developer: Visidon

Submission Date: 2021_05_18

Template size: 2052 bytes

Template time (2.5 percentile): 679 msec

Template time (median): 688 msec

Template time (97.5 percentile): 705 msec

Investigation:

Frontal mugshot ranking 137 (out of 279) -- FNIR(1600000, 0, 1) = 0.0095 vs. lowest 0.0009 from sensetime_005

Mugshot webcam ranking 119 (out of 241) -- FNIR(1600000, 0, 1) = 0.0274 vs. lowest 0.0062 from sensetime_005

Mugshot profile ranking 123 (out of 210) -- FNIR(1600000, 0, 1) = 0.8931 vs. lowest 0.0587 from xforwardai_002

Immigration visa-border ranking 82 (out of 168) -- FNIR(1600000, 0, 1) = 0.0130 vs. lowest 0.0013 from visionlabs_010

Immigration visa-kiosk ranking 85 (out of 165) -- FNIR(1600000, 0, 1) = 0.1756 vs. lowest 0.0568 from cloudwalk_hr_000

Identification:

Frontal mugshot ranking 127 (out of 279) -- FNIR(1600000, T, L+1) = 0.0785, FPIR=0.001000 vs. lowest 0.0018 from sensetime_004


Mugshot webcam ranking 113 (out of 236) -- FNIR(1600000, T, L+1) = 0.1483, FPIR=0.001000 vs. lowest 0.0122 from sensetime_003

Mugshot profile ranking 112 (out of 209) -- FNIR(1600000, T, L+1) = 0.9955, FPIR=0.001000 vs. lowest 0.1331 from cloudwalk_hr_000


Immigration visa-border ranking 79 (out of 167) -- FNIR(1600000, T, L+1) = 0.0948, FPIR=0.001000 vs. lowest 0.0047 from idemia_008

Immigration visa-kiosk ranking 57 (out of 162) -- FNIR(1600000, T, L+1) = 0.3749, FPIR=0.001000 vs. lowest 0.0996 from cloudwalk_hr_000


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime_004)




C: Evolution of accuracy for VD algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold


Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_005)




L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements.
The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates.
 The bottom panels give high threshold for more lights-out identification with low FPIR.



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: vd_002, Dataset: Border–Crossing Ageing
Threshold: 787397.000000 set to achieve FPIR(30–45, Male) = 0.001

Color encodes log(FPIR)



(The age of the highest non-mates will usually be similar to that of the probe.)

(60:99] 0.0111 0.0005

(45:60] 0.0081 0.0004

(30:45] 0.0079 0.0010

(21:30] 0.0143 0.0028

(18:21] 0.0192 0.0055

(15:18] 0.0201 0.0059

(12:15] 0.0185 0.0069

Female

Male

Sex of person in non-mate probe
(The sex of the highest non-mates will usually be that of the probe.)

Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

